




BNC Female Patch Panel – 16 Port



Part Number: E40840PL-16

This patch panel interfaces 16 individual coaxial cables via isolated 75 ohm BNC through adaptors. A bi-directional device requiring no external power. This panel has applications in telecommunications, instrumentation and video distribution.

Features:

- Mounts in standard 19" rack
- Isolated adaptors
- BNC to IEC 169-8
- Carrier quality product
- RoHS compliant
- Precision machined connectors
- Contact plating gold
- Teflon insulators
- Zinc sealed, powder coated steel
- Metal adaptor threads

OPERATING CONDITIONS

Working Temperature: -30°C to 75°C

ELECTRICAL SPECIFICATIONS

Impedance:	75 ohms
Frequency Range:	0-2GHz
VSWR:	< 1.3
Working Voltage:	< 500V RMS
Dielectric Withstand Voltage:	> 1500V RMS
Contact Resistance:	Inner Contact: < 3milliOhms Outer Contact: < 2milliOhms
Panel Isolation Voltage:	> 1kV DC

MECHANICAL SPECIFICATIONS

Coaxial Connector:	BNC female to IEC 169-8
Body:	Brass, Plated Cu/Ni5b
Pin:	Phosphor Bronze, Plated Cu/Ni5/Au
Coaxial Insulator:	Teflon
Panel Insulator:	Delrin
Mating Cycles:	500min
Panel:	Steel, Zinc Sealed and Powder Coated Black

