

AXIS T8606 Media Converter Switch 24 V DC

AXIS T8606 Media Converter Switch 24 V DC allows connection to the network using standard Ethernet or fiber optic cables that help lower the cost of installing the cameras over long distances. Perfect for city surveillance, airports and other long distance installations, AXIS T8606 is a DIN-mounted device that can convert an Ethernet signal to be used over optical fiber cable. Surveillance integrators in the field can also connect installation monitors and laptops (via the RJ45 connectors) to AXIS T8606 for camera maintenance and control. The media converter switch can be connected in a daisy chain network.

> 24 V DC IN

- > Convert Ethernet to optical fiber
- > Support for 10/100 Mbps
- > Two SFP slots and two RJ45 ports
- > Compatible with Axis network products



www.axis.com

General Supported products	All Axis network video products	Approvals	EMC EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32, KCC KN32 Class A, KN35 Safety IEC/EN 60950-1	
Casing	Metal Color: White NCS S 1002-B			
Power	24 V DC, max 3.5 W (power supply not included)			
Connectors	2x RJ45 connectors (10/100 Mbps) (Use shielded cables (STP) CAT5 or higher.) 2x SFP connectors (100/1000 Mbps) for SFP fiber optic modules or SFP to copper modules 1x power	Dimensions	150 x 100 x 30 mm (5 15/16 x 3 15/16 x 1 3/16 in)	
		Weight	284 g (0.63 lb)	
		Included accessories	Bracket Mount DIN Clip, Installation Guide	
Display and indicators	Power LED indicator Network LED indicator (4x)	Warranty	Axis 3-year warranty, see www.axis.com/warranty	
Compliance	RoHS, REACH, WEEE, CE, EN 50022, IEC 60715, AS 2756	Environmental responsibility: www.axis.com/environmental-responsibility		
Mounting	DIN Rail mount			
Environment	Indoor/Cabinet			
Operating conditions	-40 °C to 75 °C (-40 °F to 167 °F) Humidity 10-85% RH (non-condensing)			
Storage conditions	-40 °C to 75 °C (-40 °F to 167 °F) Humidity 10-85% RH (non-condensing)			



1652658/EN/M1.4/012017

SA: Marleston WA: Balcatta

1300 319 499 csd.com.au