

ISC-SK10 Shock Sensor

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Intelligent 3-axis vibration detection
- ▶ Self-learning mode
- ▶ Dual-color LED indicator
- ▶ Adjustable sensitivity
- ▶ Slim design for easy installation

The ISC-SK10 is an advanced shock sensor designed for monitoring and detecting mechanical attacks. A unique feature of the ISC-SK10 is Self-learning mode. During installation, Self-learning mode uses the sensor's LED behavior as a guide for configuring the sensitivity level.

Functions

Self-learning mode

During Self-learning mode, the sensor records and analyzes simulated vibration data within a 3 minute interval. Based on the simulated data, the sensor provides assistance for setting a suitable sensitivity level for the installation.

Adjustable sensitivity

Desired sensitivity is achieved by selecting any of four sensitivity level switches, and fine sensitivity adjustment using the potentiometer.

Dual-color LED indicator

The green LED indicates vibration, and the red LED indicates alarms. In Self-learning mode, recommended sensitivity level settings are indicated by LED behavior.

Drilling and saw detection enable

Depending on the installation, sensitivity is configurable to detect drilling, sawing, or similar type of vibration.

Certifications and approvals

Region	Certification	
Europe	CE	EN 50130-4:2011, EN61000-6-3:2007/A1:2011, EN60950-1:2006

Installation/configuration notes

Install the sensor indoors on a flat surface.

Detection range

Surface	Radius (m)	Radius (ft)
Concrete	1.5	5
Brick wall	2.5	8
Steel	3	10
Wood	3.5	11.5
Glass	3.5	11.5

Parts included

Quantity	Component
1	Sensor
1	Hardware pack
1	Installation guide

Technical specifications**Properties**

Dimensions (H x W x D)	100mm x 30mm x 20mm (3.9 in. x 1.18 in. x .78 in.)
Material	Fire protection high intensity PC enclosure

Environmental

Operating temperature	-10°C to +55°C (-14°F to +131°F)
Storage temperature	-20°C to +70°C (-4°F to +158°F)
Humidity	< 95%

Electrical

Voltage (operating)	9 to 15 VDC, 12 VDC nominal
Current	8.5 mA (standby) 12 mA (alarm)

Outputs

Alarm relay	Normally-closed (NC) relay, contacts rated for 100 mA, 30 VDC
Tamper	Normally-closed (NC) 50 mA, 30 VDC

Ordering information

ISC-SK10 Shock Sensor
Order number **ISC-SK10**