

# DS-PDPG12P-EG2-WB Wireless PIR-Glass Break Detector

■ PIR Detection Range: 12m / 85.9°

■ Glass Break Range: 8m / 120°

■ Up to 30KG pet immunity

Fully remote configurable through App

Multiple enrollment method and easy installation design

Easy replaceable battery with PCB protected





## Specification

Model		DS-PDPG12P-EG2-WB
Detection Performance	Detection Method	Passive Infrared, Acoustic Sensor
	Detection Range	12m
	Detection Angle	85.9°
	Detection Zones	52
	Detectable Speed	0.3~2m/s
	Pet Immunity	30Kg
	PIR Sensitivity	Auto,High,Pet
	White Light Filter	6500lux
	Glass Type	Float,Plate,Tampered,Wired,Laminated Leaded,Double Glazing
	Glass Break Range	8m
	Glass Thickness	2.4mm to 6.4mm
	Glass Break Sensitivity	2m,4m,6m,8m
	Digital Temperature Compensation	Support
	Glass Size	0.3m x 0.3m to 3m x 3m
	Creep Zone Protection	Support
Feature	Digital Processing	Support
	Sealed Optics	Support
	Tamper Protection	Front,Rear
	Environment Temperature Indicator	Support
	Signal Strength Indicator	Support
Interface	Power Switch	Power Up Enrolling
interrace	LED Indicator	Green(PIR),Red(BG),Blue(alarm)
Transmission	Transmission Technology	Tri-X Wireless



	Transmission Method	Two-Way RF Wireless
	Transmission Frequency	433MHz
	Transmission Security	AES-128 Encryption
	Transmission Range(Free Space)	1Km
	Frequency Hopping	Support
	Enrolling Method	Power up,Remote ID,QR Code
Electrical Characteristic s	Power Supply	Battery Powered
	Battery Type	CR123A × 2
	Typical Voltage	3V
	Standard Battery Life	4 Years
General	Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Operation Humidity	10% to 90%
	Dimension(W xHxD)	65.5mm×103mm×48.5mm
	Weight	134g
	Mounting Height	1.8 to 2.4m
	Mounting Method	Wall
	Application Scenario	Indoor
	Bracket	Optional Wall & Deciling Accessory

### Available Model

DS-PDPG12P-EG2-WB



- Accessory
- Optional

DS-PDB-IN-Ceilingbracket Internal wall mounted bracket	DS-PDB-IN-Wallbracket Internal ceiling mounted bracket



Distributed by

#### **HIKVISION**°

#### Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T +662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T+39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-[0]31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com