

A solid red horizontal bar with rounded right ends, containing the product name in white text.

DS-PDCL12-EG2
Wired Internal PIR Detector

- Digital quad pyro sensor
- Automatic sensitivity
- Wide voltage adaptation and on-board EoL resistor



▪ Specification

Model	DS-PDCL12-EG2	
Detection Performance	Detection Method	Passive Infrared
	Detection Range	12m
	Detection Angle	360°
	Detection Zones	172
	Detectable Speed	0.3~2m/s
	Sensitivity	Auto,Low
	White Light Filter	6500lux
	Digital Temperature Compensation	Support
	Creep Zone Protection	Support
Feature	Digital Processing	Support
	Sealed Optics	Support
	Tamper Protection	Front
Hardware features	Alarm output	Normally Closed
Interface	LED Indicator	Blue(Alarm)
Electrical characteristics	Power consumption	13mA Max
Electrical Characteristics	Power Supply	9 to 16 VDC
	Typical Voltage	12 VDC
General	Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Operation Humidity	10% to 90%
	Dimension(WxHxD)	φ101.2 mm x 32.9 mm
	Weight	79g
	Mounting Height	2.4 to 4m
	Mounting Method	Ceiling
	Application Scenario	Indoor

▪ Available Model

DS-PDCL12-EG2