



PROKEY WIEGAND RECEIVERS & REMOTES

Overview

With a fantastic range of up to 150m (line of sight), the ProKey remote is compatible with Wiegand or standalone relay output receivers allowing you to connect to any existing product in the market. As an optional extra the remote can be fitted with either a EM, HID, iClass or iClass HS tag for interfacing with access control systems. The site code (0-255) and number range (0-65535) of the wiegand remote is fully programmable and is custom ordered to suit the installation.

Pronto Part Number	Description
CSD-PROKEY2	2 button remote, wiegand output, with sliding drawer
CSD-PROKEY2-EM	2 button remote fitted with EM tag, wiegand output, with sliding drawer
CSD-PROKEY2-HID	2 button remote fitted with HID tag, wiegand output, with sliding drawer
CSD-PROKEY2-IC	2 button remote fitted with iClass tag, wiegand output, with sliding drawer
CSD-PROKEY2-ICHS	2 button ProKey remote, iClass High Sec tag, wiegand output, sliding drawer
CSD-PROKEY4	4 button remote, wiegand output, with sliding drawer
CSD-PROKEY4-EM	4 button remote fitted with EM tag, wiegand output, with sliding drawer
CSD-PROKEY4-HID	4 button remote fitted with HID tag, wiegand output, with sliding drawer
CSD-PROKEY4-IC	4 button remote fitted with iClass tag, wiegand output, with sliding drawer
CSD-PROKEY4-ICHS	4 button ProKey remote, iClass High Sec tag, wiegand output, sliding drawer
CSD-PROKEY-RXWI	Wiegand receiver, indoor version
CSD-PROKEY-RXWO	Wiegand receiver, outdoor version

Features:

Remote

- Stylish design
- 433.92 MHz Keeloq rolling code: 4.3 billion combinations
- Programmeable with HID Prox or EM format tags
- Long transmission range
- Indoor and outdoor receivers
- Durable product casing

Wiegand receiver

Wiegand 26 bit, 4 channels, each with an LED indicator
 Option of site-code-verification or non-code-verification (all pass through)
 433Mhz; other frequencies available on request
 Compact design; can be easily fitted into a third party cabinet

Dimensions:

CSD-PROKEY 2 Button and 4 Button Remotes

63mm (L) x 29mm (W) x 11mm (H)

CSD-PROKEY-RXWI

87mm (L) x 63mm (W) x 27mm (H)

CSD-PROKEY-RXWO

190mm (L) x 100mm (W) x 45mm (H)



Additional Information

Warranty

12 Months