

240VAC CCTV Power Supplies


EVP-224A4-P4Q EVP-224A4-P9Q EVP-224A8P16Q EVP-224D2-P4Q EVP-224D4-P9Q EVP-224D6P16Q

4 Outputs, 24VAC; 4A Supply Current 9 Outputs, 24VAC; 4A Supply Current 16 Outputs, 24VAC; 8A Supply Current 4 Outputs, 12VDC; 2A Supply Current 9 Outputs, 12VDC; 4A Supply Current 16 Outputs, 12VDC; 6A Supply Current

Note: "Supply Current" is maximum total output amperage for entire power supply.



EVP-224A4-P9Q



- 240VAC input, AC or DC output models available.
- Individually protected PTC¹-type fused outputs.
- · Individual status LED indicator.
- Main power switch with surge protection.
- · Includes enclosure and transformer.
- DC models are adjustable from 5.6~8.15 VDC or 12.6~15.15 VDC.



EVP-224D4-P9Q

Dimensions:

Specifications:

AC Models

Model No.	Outputs	Supply Current	Max Amps /Channel	Input Voltage	Output Voltages	Fuse Type
EVP-224A4-P4Q	4	4 Amp.	1.1	240VAC	24VAC	PTC ¹
EVP-224A4-P9Q	9	4 Amp.	1.1	240VAC	24VAC	PTC ¹
EVP-224A8P16Q	16	8 Amp.	1.1	240VAC	24VAC	PTC ¹

DC Models

Model No.	Outputs	Supply Current @ 12VDC	Max Amps /Channel	Input Voltage	Output Voltages	Fuse Type
EVP-224D2-P4Q	4	2 Amp.	1.1	240VAC	12VDC ²	PTC ¹
EVP-224D4-P9Q	9	4 Amp.	1.1	240VAC	12VDC ²	PTC ¹
EVP-224D6P16Q	16	6 Amp.	1.1	240VAC	12VDC ²	PTC ¹

¹Positive Temperature Coefficient ²Adjustable from 5.6~8.15 VDC & 12.6~15.15 VDC





*12.3" x 12.2" x 3.5" (312 x 310 x 89mm) only for EVP-224D6P16Q model.

7.75"(196mm) 12.3"(312mm)*

PI_240VAC_CCTV PS_0906.cdr

Copyright © 2009 Superior Electronics Corporation. All rights reserved.

Pl_240VAC_CCTV PS_0006.cdr
The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.