

# Indala Long-Range Card Reader

- Indala FlexSecur® Technology for the Industry's Most Secure Proximity Readers** - Exclusive Indala FlexSecur Password-Protected Security between card and reader screens out unauthorized cards prior to sending access control data to the host system.
- Superior Format Control for the Most Application Choices** - Indala offers card formats of up to 172 bits, and readers configurable for Wiegand, Magstripe, and Serial output formats.
- Indala Long-Range Series Readers are Part of an Expansive Product Portfolio That Meets Every Proximity Reader Requirement** - The HID Indala Proximity portfolio includes classic, mullion/slim, wallswitch, mid-range, long-range, and heavy-duty keypad readers for every application.



## ACCESS choice.

The Indala 125 kHz Long-Range product line is part of HID's latest line of highly-secure proximity readers. The HID Indala Long-Range reader, with FlexSecur® technology, has a read range of up to 26 inches and is ideal for parking applications, and other situations that require longer read ranges. These high-quality Indala Proximity Readers deliver outstanding and consistent performance with intelligent programming technology and design that matches the Indala Arch bezel.

### Exclusive FlexSecur® Security Technology

All HID Indala 125 kHz Proximity Readers feature FlexSecur technology, which provides an added level of access system security through a verification process at the reader. A feature unique to the HID Indala product line, FlexSecur screens out unauthorized cards prior to sending access control data to the host system.

This additional verification step enhances the security of your access system in two ways:

1. The entire card data field is encrypted prior to programming the card. Therefore, the data on the card cannot be decoded to determine the actual information on the card. Only the reader is able to decrypt the data and transmit it to the access control system.
2. Cards and readers can be programmed uniquely for each site, protecting the end user against unauthorized entry attempts by using cards from another facility. Again, this is unique to the HID Indala product line.

### Key Features:

- Suitable for both indoor and outdoor applications.
- Matches the HID Indala "Arch" bezel design.
- Compatible with all Indala 125 kHz cards and tags.

# Features

## Indoor / Outdoor Flexibility

All readers have weatherproof electronics assemblies, making them suitable for internal and external applications.

## Audio Tone Programming Flexibility

Standard, independently controllable audio tone is not tied to LED function.

## Compatible with Any Control Panel

Wiegand or Magnetic Stripe (Clock & Data) output easily interfaces with most existing access-control panels.

## Unbeatable Warranty and Technical Support

Customers can select HID Indala 125 kHz Proximity Readers with confidence because HID offers a lifetime product warranty and global Technical Support

## Card Programming

The ProxSmith® Programmer System and Application Programming Interface puts flexibility and convenience in the hands of OEM and security professionals. With the ability to quickly program a card or reader on site, users no longer need to rely on the factory for custom formatted cards or readers. Plus, the ProxSmith Programmer System delivers the high level of security you expect from the Indala brand.

## Long-Range Readers

<b>Mounting</b>	non-ferrous wall surface (or use 3" spacer on or near ferrous surface)
<b>Dimensions</b>	11.2"H x 11.2"W x 1.8"T (28.4 x 28.4 x 4.6 cm)
<b>Power Supply</b>	12/24VDC
<b>Current Requirements</b>	1.0A/750 mA
<b>Operating Temperature</b>	-31 to 149°F (-35 to 65°C)
<b>Operating Humidity</b>	0-95% RH, non-condensing
<b>Transmit Frequency</b>	125 kHz
<b>Certifications</b>	UL294/cUL, FCC (US), Canada, CE Mark (Europe), Australia C-Tick, New Zealand EMC
<b>Base Part Number</b>	ASR-620++
<b>Options</b>	Color - Black Selectable Output Type: Wiegand, ABA Track 2 Standard Termination: Wire Pigtail Programmable: Yes
<b>Warranty</b>	Lifetime
<b>Read Ranges*</b>	
<b>FlexISO® Card</b>	Up to 26" (66 cm)
<b>FlexISO® XT</b>	Up to 26" (66 cm)
<b>FlexCard®</b>	Up to 25" (63 cm)
<b>FlexTag™</b>	Up to 14" (35 cm)
<b>FlexKey®</b>	Up to 16" (40.64 cm)
<b>FlexISO® MIFARE®</b>	Up to 24" (61 cm)
<b>FlexISO® DESFire™</b>	Up to 24" (61 cm)
<b>FlexISO® iCLASS®</b>	Up to 24" (61 cm)

\*Note: Dependent upon installation conditions.

Specifications are subject to change without notice.  
© 2006 HID Global Corporation. All rights reserved. HID, the HID logo, Indala, ProxSmith, FlexSecur and iCLASS are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.  
MKT-LONGRANGE-DS-EN Rev. 07/06



**ACCESS** experience.

[hidcorp.com](http://hidcorp.com)

### HID Global Offices:

**Corporate North America**  
9292 Jeronimo Road  
Irvine, CA 92618-1905  
U.S.A.  
Phone: (800) 237-7769  
Phone: (949) 598-1600  
Fax: (949) 598-1690

**Asia Pacific**  
19/F 625 King's Road  
North Point  
Island East  
Hong Kong  
Phone: +852 3160-9800  
Fax: +852 3160-4809

**Latin America**  
Circunvalacion Ote. #201 B  
Despacho 2  
Col. Jardines del Moral  
Leon 37160, Gto.  
Mexico  
Phone: +52 477 779 1492  
Fax: +52 477 779 1493

**Europe, Middle East & Africa**  
Homefield Road  
Haverhill, Suffolk  
CB9 8QP  
England  
Phone: +44 (0) 1440 714 850  
Fax: +44 (0) 1440 714 840