






Axis thermal cameras

	AXIS Q29 Temperature Alarm Camera Series		AXIS Q19 Thermal Network Camera Series			
	AXIS Q2901-E	AXIS Q2901-E PT Mount	AXIS Q1942-E	AXIS Q1942-E PT Mount	AXIS Q1941-E	AXIS Q1941-E PT Mount
						
Max. video resolution	336x256	336x256	640x480	640x480	384x288	384x288
Sensor size/ Lens/ Horizontal field of view	Uncooled microbolometer Athermalized lens 9 mm, F1.25, 35° 19 mm, F1.25, 17°	Uncooled microbolometer Athermalized lens 9 mm, F1.25, 35° 19 mm, F1.25, 17°	Uncooled microbolometer Athermalized lens 10 mm, F 1.24, 63° 19 mm, F 1.23, 31° 35 mm, F 1.20, 17° 60 mm, F 1.25, 10°	Uncooled microbolometer Athermalized lens 10 mm, F 1.24, 63° 19 mm, F 1.23, 31° 35 mm, F 1.20, 17° 60 mm, F 1.25, 10°	Uncooled microbolometer Athermalized lens 7 mm, F1.18, 55° 13 mm, F1.0, 28° 19 mm, F1.23, 19.4° 35 mm, F1.2, 10.7° 60 mm, F1.25, 6.2°	Uncooled microbolometer Athermalized lens 7 mm, F1.18, 55° 13 mm, F1.0, 28° 19 mm, F1.23, 19.4° 35 mm, F1.2, 10.7° 60 mm, F1.25, 6.2°
Max. frames per second	8.3 ¹	8.3 ¹	8.3/30 ¹	8.3/30 ¹	8.3/30 ¹	8.3/30 ¹
Object temperature range	-40 °C to 550 °C (-40 °F to 1022 °F)	-40 °C to 550 °C (-40 °F to 1022 °F)	-	-	-	-
Sensitivity	NETD < 50 mK	NETD < 50 mK	NETD < 50 mK	NETD < 50 mK	NETD < 70 mK	NETD < 70 mK
Detection range (m/yd.)	-	-	10 mm: 291/318 ² 892/978 ³ 19 mm: 573/627 ² 1757/1921 ³ 35 mm: 1079/1179 ² 3307/3617 ³ 60 mm: 1833/2005 ² 5623/6149 ³	10 mm: 291/318 ² 892/978 ³ 19 mm: 573/627 ² 1757/1921 ³ 35 mm: 1079/1179 ² 3307/3617 ³ 60 mm: 1833/2005 ² 5623/6149 ³	7 mm: 200/219 ² 613/671 ³ 13 mm: 393/430 ² 1205/1318 ³ 19 mm: 567/620 ² 1739/1902 ³ 35 mm: 1028/1124 ² 3153/3448 ³ 60 mm: 1774/1940 ² 5441/5951 ³	7 mm: 200/219 ² 613/671 ³ 13 mm: 393/430 ² 1205/1318 ³ 19 mm: 567/620 ² 1739/1902 ³ 35 mm: 1028/1124 ² 3153/3448 ³ 60 mm: 1774/1940 ² 5441/5951 ³
Audio support/ Built-in mic	✓ / -	- / -	✓ / -	- / -	✓ / -	- / -
Product specific analytics (for standard analytics, see page 43)	Audio detection Standard analytics	Standard analytics	Audio detection AXIS Guard suite AXIS Video Motion Detection	AXIS Video Motion Detection	Audio detection, AXIS Guard suite, AXIS Video Motion Detection	AXIS Video Motion Detection
Power	PoE Class 3, AC, DC	PoE Class 3, AC, DC	PoE Class 3, AC, DC	PoE Class 3, AC, DC	PoE Class 3, AC, DC	PoE Class 3, AC, DC
In-/output ports	2/2	-	2/2	-	2/2	-
Operating temperature	-40 °C to 60 °C (-40 °F to 140 °F)	-40 °C to 60 °C (-40 °F to 140 °F)	-40 °C to 60 °C (-40 °F to 140 °F)	-40 °C to 60 °C (-40 °F to 140 °F)	-40 °C to 60 °C (-40 °F to 140 °F)	-40 °C to 60 °C (-40 °F to 140 °F)
Outdoor ready approvals	IP66/IP67/NEMA 4X	IP66/NEMA 4X	IP66/IP67/NEMA 4X	IP66/NEMA 4X	IP66/IP67/NEMA 4X	IP66/NEMA 4X
Zipstream/H.264/H.265	-	-	✓	✓	✓	✓
Special features	Isothermal palette Palette setting Shock detection	Isothermal palette Palette setting RS485/RS422 for pan/tilt control Shock detection	Electronic image stabilization Palette setting Shock detection	Electronic image stabilization Palette setting RS485/RS422 for pan/tilt control Shock detection	Electronic image stabilization Palette setting Shock detection	Electronic image stabilization Palette setting RS485/RS422 for pan/tilt control Shock detection

1. Up to 30 fps within EU, Norway, Switzerland, Canada, USA, Japan, Australia, New Zealand. Up to 8.3 fps in other countries. Frame rate above 9 fps may be subject to export control regulations

2. Detection range measured for humans, 1.8 x 0.5 m, calculated with Johnson's criteria

3. Detection range measured for vehicles, 4 x 1.5 m, calculated with Johnson's criteria