

305M Cat6 High Performance UTP External Cable

FEATURES:

- 305m Cat6 Black UTP External Solid Cable Roll 250MHz
- 100% Bare Copper Cable
- 23AWGx4P
- PE Jacket
- AS/CA S008:2010 Approved
- 4K UHD Ready



SPECIFICATIONS

CABLE TYPE	UTP
JACKET MATERIAL	PE
CONDUCTOR MATERIAL	BARE COPPER CABLE
INSULATION MATERIAL	HDPE
CABLE LENGTH	305M
CABLE WEIGHT	11.5KG/305M
CABLE DIAMATER	0.55
CABLE GAUGE	23AWG
JACKET THICKNESS	0.55±0.05MM
DC RESISTANCE UNBALANCED (MAX.)	IN PAIR ≤2.0%, PAIR TO PAIR≤4.0%
DC RESISTANCE (MAX.)	≤9.38Ω/100M
DIELECTRIC STRENGTH (MAX.)	DC 1000V 1MIN NO BREAKDOWN
MUTUAL CAPACITANCE AT FREQUENCY	≤5.8NF/100M
NVP	69%
OPERATING FREQUENCY	250MHZ
FLAME TEST METHOD	NO
INSTALLATION TEMPERATURE	-20 ~ +60 DEGREES CELCIUS
OPERATING TEMPERATURE	-40 ~ +75 DEGREES CELCIUS
PACKAGING	WOODEN DRUM



CENTRAL SECURITY DISTRIBUTION

An Anixter Company

1300 319 499

csd.com.au