

AXIS I8016-LVE Network Video Intercom

Compact and robust video intercom

AXIS I8016-LVE Network Video Intercom is a compact and highly robust network intercom designed for two-way communication, video identification, and remote entry control. It offers 5 MP resolution with invisible IR night vision, and exceptional audio volume with echo and noise cancellation to ensure reliable 24/7 identification even in the most demanding situations. Based on open IP standards and interfaces, this network intercom offers great integration possibilities and is a perfect complement to any video surveillance system. Furthermore, it features multiple inputs and outputs for remote control of door locks and other equipment.

- > **High-quality audio and video**
- > **Easy installation with PoE**
- > **Open interface with IP phone integration, SIP support**
- > **Outdoor-ready, vandal-resistant IK10-rated**
- > **IP66/IP69-rated with wall-mount**



AXIS I8016-LVE Network Video Intercom

Camera		Storage: disruption, recording System: system ready Time: recurrence, use schedule PTZ: moving, preset reached
Image sensor	1/2.7" progressive scan RGB CMOS	
Lens	1.95 mm, F2.2 Horizontal field of view: 140° Vertical field of view: 114° M12 mount, fixed iris	
Day and night	Automatically removable infrared-cut filter	
Minimum illumination	Color: 0.16 lux at 50 IRE, F2.2 B/W: 0.00 lux at 50 IRE, F2.2, with IR illumination on	
Shutter speed	1/50000 s to 1/5 s	
Video		
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	
Resolution	2592x1944 240x160	
Frame rate	Up to 30/25 fps (60/50 Hz) in all resolutions	
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265 Video streaming indicator	
Image settings	Saturation, contrast, brightness, sharpness, WDR, white balance, day/night threshold, tone mapping, exposure mode, exposure zones, defogging, compression, text and image overlay, polygon privacy mask	
Audio		
Audio streaming	Two-way, full duplex Echo cancellation and noise reduction	
Audio encoding	24bit LPCM, AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16 kHz Configurable bit rate	
Audio input/output	Line input, line output, built-in microphone (can be disabled), built-in speaker, automatic gain control Built-in speaker 84 dB (at 0.5 m / 20 in)	
Network		
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, protection of cryptographic keys with FIPS 140-2 certified TPM 2.0 module	
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , HTTP/2, SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, NTCIP, SIP, LLDP, Syslog	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Guardian with One-Click Connection ONVIF [®] Profile S and ONVIF [®] Profile G, specification at onvif.org	
VoIP	Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX Tested with various SIP software such as Cisco, Bria and Grandstream Tested with various PBX softwares such as Cisco, Avaya and Asterisk Contact list, parallel call forking, sequential call forking	
Event triggers	Analytics, external input, edge storage events, virtual inputs through API Call: DTMF, state, state changes Detectors: audio detection, live stream accessed, shock detection, tampering, motion alarm Hardware: Casing open, temperature, relays and outputs, network Input Signal: digital input port, manual trigger, virtual inputs	
Event actions	Axis door control Make call: SIP, API Terminate call: SIP, API Record video and audio: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS and TCP External output activation, play audio clip, overlay text, PTZ controls, status LED, WDR mode	
Data streaming	Event data	
Analytics		
Applications	Included AXIS Video Motion Detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	
General		
Casing	IP66/IP69-, NEMA 4X- and IK10-rated Stainless steel, zinc, and plastic casing Color: black NCS S 9000-N For repainting instructions of skin cover or casing and impact on warranty, contact your Axis partner. This product can be repainted	
Mounting	US 2-Gang-, 4 inch square installation boxes	
Memory	2048 MB RAM, 512 MB Flash	
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 4.7 W, max 12.7 W Relay rating: 30 V, 0.7 A	
Connectors	Shielded RJ45 10BASE-T/100BASE-TX PoE I/O: 6-pin terminal block for 2 inputs/outputs, +12V 400mA supply, and 1 relay 4-pin terminal block for audio input and output	
IR illumination	Power-efficient, long-life 940 nm IR LEDs Range of reach 5 m (16 ft) or more depending on the scene	
Storage	Support for microSD/microSDHC/microSDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com	
Operating conditions	-40 °C to 60 °C (-40 °F to 140 °F) Start-up temperature: -40 °C (-40 °F) Humidity 10–85% RH (non-condensing)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)	
Approvals	EMC EN 50121-4, EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), IEC 62236-4, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety CAN/CSA-C22.2 No. 60950-22, CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC 62471 Environment IEC 60068-2-27, IEC 60068-2-6, IEC/EN 60529 IP66/IP69, IEC/EN 62262 IK10, NEMA 250 Type 4X Network NIST SP500-267	
Dimensions	Height: 124 mm (4.9 in) Width: 124 mm (4.9 in)	
Weight	900 g (2.0 lb)	
Included accessories	Installation guide, Windows [®] decoder 1-user license, terminal block connector, Allen key (Resitorx 10)	
Optional accessories	AXIS A9801 Security Relay For more accessories, see axis.com	

Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at axis.com/vms	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).</i>
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese	Environmental responsibility: axis.com/environmental-responsibility
Warranty	5-year warranty, see axis.com/warranty	