

AXIS Washer Kit B

For clear vision all year round

AXIS Washer Kit B sprays cleaning fluid on the front window of compatible Axis positioning cameras. The kit contains a 23-liter (6-gallon) tank, a pump for delivering cleaning fluid to up to 11 m (36 ft), a hose, a nozzle and a nozzle support bracket.

- > **Sprays cleaning fluid**
- > **Delivers cleaning fluid to up to 11 m (36 ft)**
- > **23-liter tank capacity (6 gallons)**
- > **Compatible with selected Axis positioning cameras**



AXIS Washer Kit B

| General | |
|-----------------------------|---|
| Supported products | AXIS T99A10 Positioning Unit 24 V AC/DC AXIS Q8685-E/-LE PTZ Network Cameras AXIS Q87 Series |
| Casing | Tank: polyethylene Cage: stainless steel Electronics enclosure: technopolymer Nozzle support bracket: stainless steel |
| Dimensions | 301 x 410 x 348 mm (11.8 x 16.1 x 13.7 in) |
| Weight | 6.7 kg (14.8 lb) |
| Power | 230 V AC, 0.5 A, 50/60 Hz 120 V AC, 1 A, 50/60 Hz 24 V AC, 1.8 A, 50/60 Hz |
| Tank capacity | 23 l (6 gal) |
| Delivery head | Plastic hose with stainless steel nozzle |
| Tube length | 11 m (36 ft) |
| Elevation | 11 m (36 ft), 1 m/sec |
| Operating conditions | Antifreeze liquid in solution, full performance: -10 °C to 60 °C (14 °F to 140 °F) |
| Storage conditions | Antifreeze liquid in solution, reduced performance due to higher fluid viscosity at lower temperatures: -25 °C to 60 °C (-13 °F to 140 °F) |
| Storage conditions | -40 °C to 65 °C (-40 °F to 149 °F) |
| Approvals | EMC EN 50130-4, EN 61000-6-3, EN 55032 Class B, FCC Part 15 Subpart B Class B, RCM AS/NZS CISPR 32 Class B, ICES-003 Class B, VCCI Class B, EAC Safety EN 60950-1, EN 60950-22 Environment IEC/EN 60529 IP66 |
| Included accessories | Installation Guide |
| Warranty | Axis 3-year warranty, see axis.com/warranty |

Environmental responsibility:

axis.com/environmental-responsibility