

AXIS Camera Station S1132 Recorder

Out-of-the box ready server for UHD surveillance

AXIS Camera Station S1132 Recorder is an out-of-the-box ready rack server validated for reliable ultra high-definition recording. For quick and easy installation, AXIS S1132 is preconfigured and preloaded with AXIS Camera Station video management software including licenses for 32 channels plus all necessary software. The system configuration can easily be imported from AXIS Site Designer, and AXIS Camera Station lets users take full advantage of Axis wide range of video surveillance devices. With redundant enterprise-grade hard disks and power supplies, operating system stored on solid-state drive (SSD), AXIS S1132 provides high-performance and reliability for your system.

- > [Ease of installation](#)
- > [AXIS Camera Station licenses included](#)
- > [Full compatibility with Axis products](#)
- > [5-year warranty](#)



AXIS Camera Station S1132 Recorder

Licenses	32 AXIS Camera Station core licenses included, can be upgraded with additional licenses (sold separately)	General	
System scalability	Qualified for up to 48 video channels and 96 doors	Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes Operating system drive: 240 GB SSD
Hardware		Operating conditions	10 °C to 35 °C (50 °F to 95 °F) Humidity 20–80% RH (non-condensing)
Processor	Intel® Core™ i3	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Memory	8 GB	Approvals	EMC EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), RCM AS/NZS CISPR 32 Class A, VCCI Class A, KC KN 32 Class A, KC KN 35 Safety IEC/EN/UL 60950-1, EN 62368-1, NOM, BSMI, EAC
Storage	Hot swappable Enterprise Class HDD Total HDD slot: 4 Free HDD slot: 0 Out-of-the-box storage: 12 TB after RAID 5 Out-of-the-box capacity without RAID: 16 TB (4x4 TB)	Dimensions	596 x 484 x 43 mm (23.47 x 19.06 x 1.7 in), 1U chassis
RAID	Factory RAID level: 5 RAID levels: 0, 1, 5, 6, 10	Weight	13.5 kg (29.7 lb)
Power	2 x 350 W hot-plug redundant power supplies (included) (100 - 240 V AC, 50/60 Hz, 4.8 - 2.4 A)	Included accessories	Rack rails, 2x C13 to C14 power cords for rack PDU (Wall plug power cords are not included)
Connectors	Front side: 1x USB 2.0 Rear side: 2x USB 2.0 2x Ethernet (RJ45) 1 GbE 1x VGA 1x Serial port	Optional accessories	Axis desktop terminals For more accessories, see axis.com
Video		Warranty	5-year warranty, see axis.com/warranty
Video streaming	Not intended for local viewing of video. Recommended to use AXIS desktop terminals.		
Recording	Qualified for recording up to 48 video channels with a total recording rate up to 384 Mbit per second.		

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility