

AXIS Camera Station S1132 Tower Recorder

Out-of-the-box ready server and client for UHD surveillance

AXIS Camera Station S1132 Tower Recorder is an out-of-the-box ready-to-use server and client in tower form factor, validated for reliable ultra-high-definition recording and monitoring. It comes preconfigured and preloaded with AXIS Camera Station including licenses for 32 channels, as well as all the necessary software. The system configuration can be imported from AXIS Site Designer and AXIS Camera Station lets users take advantage of the wide range of Axis video surveillance devices. With redundant enterprise-grade hard drives and power supplies, operating system stored on solid-state drive (SSD) and built-in operating system recovery, AXIS S1132 Tower provides high-performance and reliability for your system.

- > **Flexible storage options including RAID**
- > **Optimized for Axis network products**
- > **Quick system setup and intuitive operation**
- > **Validated with extensive support**
- > **AXIS Camera Station licenses included**



AXIS Camera Station S1132 Tower Recorder

Models	AXIS S1132 Tower 32 TB AXIS S1132 Tower 64 TB	4 split x 1080p at 30 fps 9 split x 720p at 15 fps 24 split x 360p at 15 fps Any combination of the above for maximum two 4K monitors
Licenses	32 AXIS Camera Station core licenses included, can be upgraded with additional licenses (sold separately)	Playback: Supports one monitor with the same split scenarios as for live view.
System scalability	Qualified for up to 48 video channels and 96 doors	
Hardware		
Processor	Intel® Core™ i3	
Memory	16 GB (2x8 GB)	
Storage	S1132 Tower 32 TB Hot swappable Enterprise Class HDD Total HDD slot: 8 Free HDD slot: 4 Out-of-the-box storage: 24 TB after RAID 5 Out-of-the-box capacity without RAID: 32 TB (4x8 TB) S1132 Tower 64 TB Hot swappable Enterprise Class HDD Total HDD slot: 8 Free HDD slot: 0 Out-of-the-box storage: 56 TB after RAID 5 Out-of-the-box capacity without RAID: 64 TB (8x8 TB)	
RAID	Factory RAID level: 5 RAID levels: 0, 1, 5, 6, 10, JBOD	
Graphic card	Nvidia® Quadro®	
Power	Up to 2 x 495 W hot-plug redundant power supplies (100 - 240 V AC, 50/60 Hz, 6.5 - 3.0 A)	
Connectors	Front side: 1x USB 3.1 Rear side: 2x USB 3.1 4x USB 2.0 2x Ethernet (RJ45) 1 GbE 3x Mini DisplayPort™ (max two monitors recommended)	
Video		
Video streaming	Live view: 1 stream x 4K at 30 fps	
Recording	Qualified for recording up to 48 video channels with a total recording rate up to 384 Mbit per second.	
General		
Operating system	Microsoft® Windows® 10 IoT Enterprise SAC Built-in operating system recovery: yes Operating system drive: SSD	
Operating conditions	10 °C to 35 °C (50 °F to 95 °F) Humidity 10–80% RH (non-condensing)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)	
Approvals	EMC EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), RCM AS/NZS CISPR 32 Class A, VCCI Class A, KC KN 32 Class A, KC KN 35 Safety IEC/EN/UL 60950-1, EN 62368-1, NOM, BSMI, EAC	
Dimensions	218 x 603 x 430 mm (8.59 x 23.75 x 16.93 in)	
Weight	S1132 32 TB 22.9 kg (50.5 lb) S1132 64 TB 26.5 kg (58.4 lb)	
Included accessories	2x C13 wall plug power cord, 2x Mini DisplayPort™ to DisplayPort™ adapter	
Optional accessories	Axis joysticks and control boards For more accessories, see axis.com	
Warranty	5-year warranty, see axis.com/warranty	

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:
axis.com/environmental-responsibility