

DS-K1T341CMFW Face Recognition Terminal



Face recognition terminal adopts deep learning algorithm, which helps to recognize the face faster with higher accuracy. It also supports multiple authentication modes: face/card/fingerprint/PIN authentication, etc. It can be applied in multiple scenarios, such as buildings, enterprises, financial industries, and other important areas.

- Deep learning algorithm
- 4.3-inch capacitive touch screen, 2 MP wide-angle dual-lens
- 3,000 face capacity, 3,000 card capacity, 3,000 fingerprint capacity and 150,000 event capacity
- Multiple authentication modes, including face, fingerprint and card, etc.
- Face recognition duration < 0.2 s/User
- Supports mask wearing detection
- Connects to external access controller or Wiegand card reader via Wiegand protocol
- Connects to secure door control unit via RS-485 protocol to avoid the door opening when the terminal is destroyed
- Two-way audio with client software, door station, indoor station, and main station



Specification


Specification			
Display			
Screen size	4.3 inch		
Operation method	Capacitive touch screen		
Туре	IPS		
Video			
Lens	2		
Resolution	2 MP (video stream: 720P)		
FOV	HFOV = 41.5°; VFOV = 75.5°; DFOV = 87°		
Audio			
Audio quality	Noise suppression and echo cancellation		
Network			
Wired network	Support		
Wi-Fi	Support, 2.4 G, 802.11b/g/n		
Interface			
Network interface	1 RJ-45, 10/100 M self-adaptive		
Lock control	1		
Exit button	1		
Door contact input	1		
TAMPER	1		
RS-485	1,RS-485 (Half duplex,HIKVISION)		
Wiegand	1, Wiegand (Hik 26bit, Hik 34bit)		
USB	1		
Authentication			
Card type	M1 card		
General			
Built-in access controller	Support		
Power supply	12 VDC to 24 VDC, 2 A		
Power consumption	≤ 10 W		
Working temperature	-30 °C to 60 °C (-22 °F to 140 °F)		
Protective level	IP65		
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil), Korean		
Function			
Hik-Connect	Support		
QR code recognition	Support		
Face anti-spoofing	Support		
1 0			


Available Model

DS-K1T341CMFW

Dimension









Accessory

Optional

DS-KAB6-D1 Base Bracket	DS-KAB6-ZU1 Brackets for face terminals	DS-KAB671-P2 Stand Stick	DS-KAB34X-S1 Protective Shield
7			



Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ



Hikvision Corporate Channel



6 hikvisionhq